

WZ1001 Clamp-on Current Transformer

3-447-026-03 1/3.21

- Safe in compliance with IEC 61010
- Minimal transformation error
- · Large jaw opening with 43 mm dia.
- · Compact and handy
- Permanently connected safety cable



Application

The clamp-on current transformer allows for the interruption-free measurement of alternating current by enclosing the electrical conductor or busbar.

The clamp-on current transformer is especially suited as accessory for measurements with the clipping multimeter METRALINE DM 61.

Applicable Regulations and Standards

IEC 61010-1 EN 61010-1 VDE 0411-1	Safety requirements for electrical equipment for measurement, control and laboratory use	
EN 61010-2-032	Particular requirements for hand-held and hand- manipulated current sensors for electrical test and measurement	
EN 60529 VDE 0470-1	Test instruments and test procedures Protection provided by enclosures (IP code)	
IEC 61 326/EN 61 326	Electromagnetic Compatibility (EMC)	

Characteristic Values

Nominal primary current	1 1000 A AC	
Output signal	1 mA AC / 1 A AC	
Transmission ratio Input: output	1000 : 1	
Accuracy / max.error	Class 1 (2.5 VA) (for current range from 1 A to 1000 A, 50 Hz)	
Max. operating voltage	CAT III 600 V per IEC 61010	
Frequency range	40 Hz 1 kHz	
Jaw opening / conductor diameter	max. 43 mm	
Dimensions (W x H x D)	92 x 39 x 220 mm	
Weight	approx. 650 g	
Cable length	1.5 m	

Standard Equipment

- 1 Clamp-on current transformer with connection cable and 4 mm safety plugs
- 1 Operating instructions

Order Information

Description	Туре	Article number
Clamp-on current transformer		
1000:1	WZ1001	Z194A

WZ1001 Clamp-on Current Transformer

© Gossen Metrawatt GmbH

Edited in Germany • Subject to change, errors excepted • PDF version available on the Internet

All trademarks, registered trademarks, logos, product names, and company names are the property of their respective owners.



Telefon +49 911 8602-111 Telefax +49 911 8602-777

E-Mail info@gossenmetrawatt.com

www.gossenmetrawatt.com